

Palang Parkir



MEGAH SAKTI MAKMUR. CV

SALES, SERVICE & SPARE PART : PARKING SYSTEM - AUTOGATE, OUTDOOR AND BARRIER GATE

SIUP:510/2-CW46/BPPT, TDP :10113425351, NPWP : 72.618.987.1-429.000



MSM-DC 310Y

CREATING
A NEW GENERATION
OF HIGH-SPEED
BARRIER GATE
THAT'S BETTER
BY ANY MEASURE

OFFICE CENTER :
JL. CIJAURA GIRANG III
NO. 36/2E, BUAH BATU
BANDUNG - WEST JAVA
PHONE : +6285 100 956 600
E-MAIL : cvmsmbandung@gmail.com
WEB : www.msm-cv.com



MSM-DC 310 Y - Isn't simply faster — it's better in every way. Larger, yet dramatically handier. More powerful, but remarkably power efficient . With a smooth metal surface that seamlessly meets the new digital stepping motor. It's one continuous form where hardware and drivers function in perfect unison, creating a new generation of high-speed barrier gate that's better by any measure.

Straight Boom Length	2 m - 3 m
Opening and Closing Time	1.2 s
Voltage	220 V / 110 V + _10%
Frequency	60 HZ / 50 HZ
Motor Power Consumption	120 w
Working Temperature	-40 °C To 85 °C
Housing Dimension	1000 (H)* 300 (W)* 240 (D) mm
Base Dimension	347 (W)* 364 (D) mm
Weight Not Including Barrier Boom	75 kgs
Drive	Torque Motor
Maximum Remote Control Distance	30 m

COMPLETENESS :



1. International Brand Coating (AkzoNobel)



2. Motor, Springs, Limited Switch (Work Strong + Stable Working)



3. Pole Protection, Anti-Smashing + Warning



4. Mark Of Attention Safety



5. Control Panel



6. Remote Control

Barrier gate dgn kualitas tinggi barrier gate nice kualitas tinggi barrier gate BFT

GIOTTO



- Unit kontrol yang terletak di posisi yang mudah diakses dan terpisah dari bagian mekanik
- Batasi sistem switch dengan penyesuaian elektronik yang mempercepat instalasi dan memastikan presisi maksimum dalam gerakan.
- Sistem power supply baterai cadangan, diinstal Unit on-board.

Technical drawing



Barrier dengan 24V power supply untuk pembukaan yang jelas hingga 6m dan membuka waktu 4sec. Dampak perlawanan dengan cara Encoder. Abu-abu RAL 7015 +