

# Palang Parkir



## **MEGAH SAKTI MAKMUR. CV**

SALES, SERVICE & SPARE PART : PARKING SYSTEM - AUTOGATE, OUTDOOR AND BARRIER GATE

SIUP:510/2-CW46/BPPT, TDP :10113425351, NPWP : 72.618.987.1-429.000

### **MSM-DC 310Y**

CREATING  
A NEW GENERATION  
OF HIGH-SPEED  
BARRIER GATE  
THAT'S BETTER  
BY ANY MEASURE



#### **OFFICE CENTER :**

JL. CIJAJURA GIRANG III  
NO. 36/2E, BUAH BATU  
BANDUNG - WEST JAVA

PHONE : +6285 100 956 600

E-MAIL : [cvmsmbandung@gmail.com](mailto:cvmsmbandung@gmail.com)

WEB : [www.msm-cv.com](http://www.msm-cv.com)



**MSM-DC 310 Y** - Isn't simply faster — it's better in every way. Larger, yet dramatically handier. More powerful, but remarkably power efficient . With a smooth metal surface that seamlessly meets the new digital stepping motor. It's one continuous form where hardware and drivers function in perfect unison, creating a new generation of high-speed barrier gate that's better by any measure.

<b>Straight Boom Length</b>	<b>2 m - 3 m</b>
<b>Opening and Closing Time</b>	<b>1.2 s</b>
<b>Voltage</b>	<b>220 V / 110 V + _10%</b>
<b>Frequency</b>	<b>60 HZ / 50 HZ</b>
<b>Motor Power Consumption</b>	<b>120 w</b>
<b>Working Temperature</b>	<b>-40 °C To 85 °C</b>
<b>Housing Dimension</b>	<b>1000 (H)* 300 (W)* 240 (D) mm</b>
<b>Base Dimension</b>	<b>347 (W)* 364 (D) mm</b>
<b>Weight Not Including Barrier Boom</b>	<b>75 kgs</b>
<b>Drive</b>	<b>Torque Motor</b>
<b>Maximum Remote Control Distance</b>	<b>30 m</b>

**COMPLETENESS :**



**1. International Brand Coating (AkzoNobel)**



**2. Motor, Springs, Limited Switch (Work Strong + Stable Working)**



**3. Pole Protection, Anti-Smashing + Warning**



**4. Mark Of Attention Safety**



**5. Control Panel**



**6. Remote Control**

Barrier gate dgn kualitas tinggi barrier gate nice kualitas tinggi barrier gate BFT

# GIOTTO



- Unit kontrol yang terletak di posisi yang mudah diakses dan terpisah dari bagian mekanik
- Batasi sistem switch dengan penyesuaian elektronik yang mempercepat instalasi dan memastikan presisi maksimum dalam gerakan.
- Sistem power supply baterai cadangan, diinstal Unit on-board.

## Technical drawing



**Barrier** dengan 24V power supply untuk pembukaan yang jelas hingga 6m dan membuka waktu 4sec. Dampak perlawanan dengan cara Encoder. Abu-abu RAL 7015 +